Control Technology Technical Data Sheet

Alpha IP: Key Ring Remote Control – alarm KRCA 63001-N3

The Alpha IP Key Ring Remote Control – Alarm allows to control alarm functions, or the switching of lighting systems. The alarm functions can be configured in the Alpha IP app. These functions can be activated and deactivated with the keys of the key ring remote control.



1.1 Product characteristics

- Wireless remote control with four buttons for convenient control of alarm functions or turning lighting on or off
- Alarm functions can be created via the Alpha IP app and enabled or disabled via the wireless remote control at the touch of a button
- Function keys for "Outer protection", "Full protection", "Alarm disarmed" and "Light on/off"
- · Attach to keyring for easy access at any time
- Long battery life thanks to the use of a standard AAA battery
- Glass fibre-reinforced and halogen-free material for optimum durability and environmental compatibility
- Direct confirmation of wireless commands via the multicolour device LED

1.2 Scope of supply

- Alpha IP Key Ring Remote Control alarm
- Key ring
- 1.5 V LR03/micro/AAA battery
- · Operating instructions

2 Technical Data

Supply voltage	1x 1,5 V LR03/Micro/AAA
Power consumption	100 mA max.
Battery service life	2 years (typ.)
Protection type	IP20
Ambient temperature	-10 bis 55 °C
Dimensions (W x H x D)	38 x 75 x 14 mm
Weight	38 g (including batteries)
Radio frequency	868,3 MHz/869,525 MHz
Typical radio free-field range	200 m
Packaging dimensions	122 x 93 x 36 mm
Packaging weight	104 g

